



APOGEE
design systems

Apogee Design Support Center

User Manual: Select Fields

Select and Select*

Both `select` and `select*` represent a drop-down menu (`<select>` in HTML). `select*` requires the user to select at least one option from the menu.

| Option | Examples | Description |
|-----------------------------|--|--|
| <code>id:(id)</code> | <code>id:foo</code> | id attribute value of the select element. |
| <code>class:(class)</code> | <code>class:bar</code> | class attribute value of the select element. To set two or more classes, you can use multiple class: option. |
| <code>tabindex:(num)</code> | <code>tabindex:10</code> | tabindex attribute value of the select element. |
| <code>default:(num)</code> | <code>default:2</code> <code>default:1_2_3</code> | Pre-selected options. The integer following default: is the position in the order of items. 1 is the first one. If you want to make two or more items selected, joint integers with underbar (<code>_</code>), as <code>default:1_2_3</code> . |
| <code>multiple</code> | | Make drop-down menu multi-selectable. |
| <code>include_blank</code> | | Insert a blank item into the top of options of this drop-down menu. |
| <code>first_as_label</code> | | Use the first value as a label. |

Available options for `select` and `select*`

These types of tags have one or more values, and the values will be used as options in the drop-down menu.

Example:

```
[select your-country "China" "India" "San Marino"]
```